

MPN: PROHDMIHD15-18G

Pro HDMI-kabel 15m

Hoge prestaties en hoge snelheid HDMI 2.0 18Gbit-kabel met Ethernet.

Ondersteunt resoluties tot 4K@60Hz met HDCP 2.2, CEC en ARC
Ultra flexibel. Belangrijk: Niet bi-directioneel. Slechts één richting.

Opmerking: Deze kabel is voorzien van een HDMI-slot. Dit zorgt voor een stabiele en veilige verbinding tussen AV-apparatuur (bijv. AV-splitters, schakelaars of andere AV-distributieapparatuur) in vaste installaties. Voeg de PROHDMIHDMFM2-kabel toe wanneer u deze kabelverbinding gebruikt met een laptop of andere draagbare apparaten. Deze kabel beschermt de interface in uw draagbare apparaat, zodat deze niet beschadigd raakt bij het in- en uitpluggen meerdere keren.

- Alle HDMI-resoluties tot 4K (4096x2160p @60Hz), inclusief 3D-video
- Ondersteunt samplefrequentie 4:4:4
- Hoge dynamische bereik (HDR)
- Overdrachtsnelheid 18 Gbit/s
- HDCP 2.2
- Ondersteunt Deep Color, tot 16-bits per kanaal, inclusief x.v.Color-standaard
- Ondersteunt de 21:9 bioscoopverhouding
- Ondersteunt SA-CD, DVD-Audio, DTS-HD Master Audio, Dolby TrueHD en andere hoge definitie audio-standaarden
- Audio Return Channel
- Auto Lip Sync



Specificaties

Features	3D	Yes
	Audio Return Channel (ARC)	Yes
	AWG wire size	28
	Cable jacket material	Polyvinyl chloride (PVC)
	Cable length	15 m
	Cable material	Copper
	Cable shielding	Aluminum mylar foil
	Colour depth	16 Bit
	Connector 1	HDMI
	Connector 1 form factor	Straight
	Connector 1 gender	Male
	Connector 2	HDMI
	Connector 2 form factor	Straight
	Connector 2 gender	Male
	Connector contacts plating	Gold
	Data transfer rate	18 Gbit/s
	Dolby technologies	DTS-HD Master Audio
	HDCP	Yes
	HDCP version	2.2

Features	HDMI Ethernet channel	Yes
	HDMI version	2.0
	High Dynamic Range (HDR) supported	Yes
	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
	High Dynamic Range 10 (HDR10)	Yes
	Maximum refresh rate	60 Hz
	Maximum resolution	3840 x 2160 Pixels
	Plug and Play	Yes
	Product colour	Black
	Pull-off force	2 kg
	Pull-resistant connector(s)	Yes
	Quantity per pack	1 stuk(s)
	RGB support	4:4:4
	RoHS compliance	Yes
	Supported graphics resolutions	4096 x 2160
	Supported video modes	2160p
Logistics data	Master (outer) case height	2,6 cm
	Master (outer) case width	3,85 cm
Operational conditions	Operating temperature (T-T)	-20 - 60 °C
Other features	Cable colour	Black
	Package weight	8,9 kg
	Quantity per box	6 stuk(s)
Vendor information	Brand Name	Vivolink
	Warranty	12 Ja(a)r(en)
Weight & dimensions	Cable diameter	7,3 mm

Andere producten in deze serie

Cable length	Black	White
0,25	PROHDMIHD0.25	
0,5	PROHDMIHD0.5	PROHDMIHD0.5W
1,0	PROHDMIHD1	PROHDMIHD1W
1,5	PROHDMIHD1.5	PROHDMIHD1.5W
2,0	PROHDMIHD2	PROHDMIHD2W
3,0	PROHDMIHD3	PROHDMIHD3W
5,0	PROHDMIHD5	PROHDMIHD5W
7,5	PROHDMIHD7.5	PROHDMIHD7.5W
10,0	PROHDMIHD10-IDG	PROHDMIHD10W
12,5	PROHDMIHD12.5	
15,0	PROHDMIHD15-18G	PROHDMIHD15W
20,0	PROHDMIHD20-18G	PROHDMIHD20W