

TOUCH			
Type:	Ultra Fine Touch Technology (IR Recognition)	Eenvoudig delen via LAN tussen IFP en slot-in-apparaat:	10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000)
Touch resolutie:	32767x32767	Light Sensor:	Yes
Touch punt:	Up to 64 points of touch	PIR Sensor:	Yes
Palm Rejection:	Yes	STROOM	
INPUT		Spanning:	100-240V AC +/- 10% Wide Range
HDMI:	x3 (Frontx1:HDMI2.1 with CEC ; Rearx2: [(HDMI2.1 with CEC, ARC)x1+(HDMI2.1 with CEC)x1]	Consumptie:	On: 92.44 W ; Off:< 0.5 W
RGB/VGA:	x1	ERGONOMICS	
DisplayPort:	x1	Wandmontage (VESA®):	800 x 400
Audio:	x1	OPERATING CONDITIONS	
RS232:	x1	Temperatuur (° C):	0°C to 40°C
SD/SDHC:	TF Card Slot(Micro SD)	Luchtvochtigheid:	20% ~ 80% RH non-condensing
OPS:	x1 PC Slot	AFMETINGEN (B X H X D)	
OUTPUT		Fysiek (inch/mm):	67.21 x 40.58 x 3.44 in / 1709.1 x 1030.8 x 87.4 mm
HDMI:	x1 (HDMI 2.1 4K@60Hz)	Verpakking (inch / mm):	72.95 x 45.35 x 6.93 in / 1853 x 1152 x 176 mm
Audio:	x1 (Line out)	WEIGHT	
SPDIF:	x1 (Optical)	Netto (lb / kg):	101.2 lb / 45.9 kg
LAN		Bruto (lb/kg):	128.09lb / 58.1 kg
RJ45:	x2	REGULATIONS	
		cTUVus, EPEAT Silver, BSMI, TGM, LBL, FF, REACH , WEEE, FCC_ICES003, ES8.0, CE_EMC, CB, EAC, UKrErP-EEL	
		ENERGY STAR VERSIE	
		8.0	